



KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX F5868 / F5888, OPTICAL, CANOPEN, Ø58 MM SERIE F5868 CANOPEN

- Housing diameter Ø58 mm
- CANopen - Interface
- 16 + 16 bit resolution
- -40 to +85 ° C working temperature



Product description

Sendix F5868 / F5888 is a series of multivalved optical axes and hole axes with CANopen interface and resolution of up to 32 bits (16 bit multi-color + 16-bit one-turn).

The sensor also has high enclosure, shock resistance and a wide temperature range. The F5868 / F5888 is therefore very suitable for applications where extreme environments or temperatures may occur, such as mobile applications.

Please refer to the image below for ordering information.

Order code		8.F5868 . XX2X . 21 2X						
Shaft version		Type	a	b	c	d	e	f
a Flange	1 = clamping flange, IP65	ø 58 mm [2.28"]						
	3 = clamping flange, IP67	ø 58 mm [2.28"]						
	2 = synchro flange, IP65	ø 58 mm [2.28"]						
	4 = synchro flange, IP67	ø 58 mm [2.28"]						
b Shaft (ø x L), with flat	1 = 6 x 10 mm [0.24 x 0.39"] ¹⁾							
	2 = 10 x 20 mm [0.39 x 0.79"] ²⁾							
	3 = 1/4" x 7/8"							
	4 = 3/8" x 7/8"							
c Interface / power supply	2 = CANopen DS301 V4.02 / 10 ... 30 V DC							
d Type of connection	A = radial cable, 2 m [6.56'] PVC							
	B = radial cable, special length PVC *)							
	E = 1 x radial M12 connector, 5-pin							
	F = 2 x radial M12 connector, 5-pin							
*) Available special lengths (connection type B):								
3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21']								
order code expansion .XXXX = length in dm								
ex.: 8.F5868.122B.2123.0030 (for cable length 3 m)								

Order code

Hollow shaft

8.F5888

Type

a

b

c

d

e

f

XX2X

212X

a

Flange

1 = with spring element, long, IP65

2 = with spring element, long, IP67

3 = with stator coupling, IP65 ø 65 mm [2.56"]

4 = with stator coupling, IP67 ø 65 mm [2.56"]

5 = with stator coupling, IP65 ø 63 mm [2.48"]

6 = with stator coupling, IP67 ø 63 mm [2.48"]

b

Through hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

6 = ø 15 mm [0.59"]

Blind hollow shaft

(insertion depth max. 30 mm [1.18"])

B = ø 12 mm ¹⁾

c

Interface / power supply

2 = CANopen DS301 V4.02 / 10 ... 30 V DC

d

Type of connection

L = tangential cable, 2 m [6.56'] PVC

M = tangential cable, special length PVC *)

E = 1 x radial M12 connector, 5-pin

F = 2 x radial M12 connector, 5-pin ²⁾

*) Available special lengths (connection type M):

3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21']

order code expansion .XXXX = length in dm

ex.: 8.F5888.542M.2123.0030 (for cable length 3 m)

e

Fieldbus profile

21 = CANopen

f

Options (service)

2 = no option

3 = SET button

Optional on request



- Ex 2/22 ³⁾ (not for type of connection L, M)

- surface protection salt spray tested

Specifications

Connection Thread	Cable, M12
Housing diameter	58
IP Class	IP65, IP67
Mounting	Shoulder
Output	CANopen
Resolution Envarv	Max: 16 bit, default: 13 bit
Resolution More Yards	16 bit
Sensor type	Absolute
Shaft Diameter max	10
Shaft Diameter min	6
Supply Voltage DC Max	30
Supply Voltage DC Min	10
Temperature range from	-40
Temperature range to	85
Version	Multiturn

Interface	Type of connection	Function	Collective terminal cover with terminal block	Signal	0 V	+V	CAN_L	CAN_H	CAN_GND
2	A, B, L, M	Bus IN	Signal	0 V	+V	CAN_L	CAN_H	CAN_GND	
		Abbreviation	Signal	0 V	+V	CL	CH	CG	
		Cable colour	Signal	WH	BN	YE	GN	GY	
		Pin	Signal	3	2	5	4	1	
		Bus OUT	Signal	0 V	+V	CAN_L	CAN_H	CAN_GND	
		Abbreviation	Signal	0 V	+V	CL	CH	CG	
		Pin	Signal	3	2	5	4	1	
		1 x M12 connector	Signal	0 V	+V	CAN_L	CAN_H	CAN_GND	
		Abbreviation	Signal	0 V	+V	CL	CH	CG	
		Pin	Signal	3	2	5	4	1	

Interface	Type of connection	Function	Cables (Bus terminal cover with terminal box)						
2	A, B, L, M	Bus IN	Signal:	0 V	+V	CAN_L	CAN_H	CAN_GND	
			Abbreviation:	power supply	power supply				
			Abbreviation:	0 V	+V	CL	CH	CG	
			Cable colour:	WH	BN	YE	GN	GY	
Interface	Type of connection	Function	2 x M12 connector						
2	F	Bus IN	Signal:	0 V	+V	CAN_L	CAN_H	CAN_GND	
			Abbreviation:	power supply	power supply				
			Abbreviation:	0 V	+V	CL	CH	CG	
			Pin:	3	2	5	4	1	
		Bus OUT	Signal:	0 V	+V	CAN_L	CAN_H	CAN_GND	
			Abbreviation:	power supply	power supply				
			Abbreviation:	0 V	+V	CL	CH	CG	
			Pin:	3	2	5	4	1	
Interface	Type of connection	Function	1 x M12 connector						
2	E	Bus IN	Signal:	0 V	+V	CAN_L	CAN_H	CAN_GND	
			Abbreviation:	power supply	power supply				
			Abbreviation:	0 V	+V	CL	CH	CG	
			Pin:	3	2	5	4	1	