



KUEBLER - ABSOLUTE-CODED ANGULAR TRANSMITTER SENDIX F5868 / F5888, OPTICAL, ETHERNET/IP, Ø58 MM

SERIE F5888 ETHERNET/IP

- Housing diameter Ø58 mm
- EtherNet/IP
- Safety-Lock™
- Quick startup



Product description

Sendix F5868 / F5888 is a multivalued fieldbus transducer with EtherNet / IP in robust design. Thanks to the construction of Safety-Lock™ as well as the fully cast housing, the sensor is able to handle even the more demanding applications where there are high demands on the sensor. The wide temperature range combined with the high enclosure class allows the sensor to be used outdoors as well as applications where large temperature changes occur. Sendix F5868 / F5888 comes with LED indication which facilitates diagnosis of the sensor.

Please refer to the images below for ordering information.

Order code Shaft version	8.F5868	.XXAN.	A222	
	Type	a b c d	e	
a Flange		b Shaft (ø x L), with flat	c Interface / Power supply	e Fieldbus profile
1 = clamping flange, IP65 ø 58 mm [2.28"]		1 = 6 x 10 mm [0.24 x 0.39"]	A = EtherNet IP / 10 ... 30 V DC	A2 = EtherNet/IP
2 = synchro flange, IP65 ø 58 mm [2.28"]		2 = 10 x 20 mm [0.39 x 0.79"]	d Type of connection	Optional on request
5 = square flange, IP65 □ 63.5 mm [2.5"]		3 = 1/4" x 7/8"	N = 3 x axial M12 connector, 4-pin	- Ex 2/22
		4 = 3/8" x 7/8"		

Order code Hollow shaft	8.F5888	.XXAN.	A222	
	Type	a b c d	e	
a Flange		b Blind hollow shaft	c Interface / Power supply	e Fieldbus profile
1 = with spring element long, IP65		(insertion depth max. 30 mm [1.18"])	A = EtherNet IP / 10 ... 30 V DC	A2 = EtherNet/IP
3 = with stator coupling, IP65 ø 65 mm [2.56"]		A = ø 10 mm [0.39"]	d Type of connection	Optional on request
5 = with stator coupling, IP65 ø 63 mm [2.48"]		B = ø 12 mm [0.47"]	N = 3 x axial M12 connector, 4-pin	- Ex 2/22
		C = ø 14 mm [0.55"]		
		D = ø 15 mm [0.59"]		
		E = ø 3/8"		
		F = ø 1/2"		

Specifications

Connection Thread

M12

Housing diametre	58
IP Class	IP65
Mounting	Hollow shaft
Output	EtherNet/IP
Resolution More Yards	Max. 16 bit
Sensor type	Absolute
Shaft Diameter max	15
Shaft Diameter min	10
Supply Voltage DC Max	30
Supply Voltage DC Min	10
Temperature range from	-40
Temperature range to	80
Version	Multiturn

