


EARTH TERMINALS - PSL 1.5-10MM

PSL

27013.2

Terminal Block PSL4/2A 4sq, GNYE, Push In

- Snap on
- 2 to 4 connections
- Pluggable cross connectors
- Push button cable release
- Test pick off point



Product description

The compact and innovative connectors ensure high current carrying capacity, a pull-resistant connection and a very stable fixing to the DIN rail. The new bushing and protective earthing connectors are available in six cross-sectional areas from 1.5 mm² to 16 mm², with 2, 3 and 4-conductor connection options with conductor areas from 0.34 mm² to 25 mm². Two- and three-layer connectors are also available for this new range. PSL connectors are DIN-rail pluggable earthing connectors, available in 2, 3 and 4-pole up to a nominal wire size of 16mm².

Specifications

Color	Green/yellow
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	0.2
Cross section single wire to	6
Cross section stranded wire from	0.2
Cross section stranded wire to	4
Cross section stranded with ferrule from	0.25
Cross section stranded with ferrule to	4
Cross-Section	4
Flamklass	UL94-V0

Height	35.2
Height TS 35/7.5	36.7
Insulation Material	Polyamide 6.6
Length	56
Mounting	Mounting rail TS 35/7.5
Number of levels	1
Number of terminals per level	2
Operating temperature from	-40
Operating temperature to	120
Overvoltage category	III
Pack Size	50
Plug gauge acc. EN 60 947-1	A4
Rated impulse voltage	8
Rated wire cross section from	24
Rated wire cross section to	10
Stripping Length	12
Tariff code	85369010
Weight	12.2
Width	6.1

