

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

1001.0

RK 2.5-4 Brown, 4mm² Feed through, multi-foot

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



Product description

Specifications

Approvals	UL, CSA, GL, KEMA KUR, EAC
Color	Brown
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	0.2
Cross section single wire to	6
Cross section stranded wire from	0.2
Cross section stranded wire to	6
Cross section stranded with ferrule from	0.2
Cross section stranded with ferrule to	4
Cross-Section	4
CSA test standard	C22.2 No 158
EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2

GL test standard	IEC 60947-7-1:2002
Height TS 32	51.5
Height TS 35/7.5	47
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	48
Mounting	TS 35 and TS 32
Number of levels	1
Number of test pick off options	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	100
Plug gauge acc. EN 60 947-1	A4
Rated Current CSA	40
Rated Current IEC	32
Rated impulse voltage	8
Rated wire cross section from (AWG)	22
Rated wire cross section to (AWG)	11
Rated Voltage IEC	800
Screw size	M 3
Screw type	Slotted
Stripping Length	12
Tariff code	85369010
Torque max	1
Torque Min	0.5
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	10.42
Width	6
Voltage CSA	600

