

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

1120.2

Terminal Block RK 50sq Beige, Fully Enclosed

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



Product description

Specifications

Additional information	with housing pegs and allen screws
Approvals	UL, CSA, GL, CSA US, KEMA KUR, EAC
Banded wire up to	11.8 x 5.0 mm
Color	Beige
Connections	2
Contamination degree	3
Country of origin	CZ
Cross section single wire from	16
Cross section single wire to	50
Cross section stranded wire from	25
Cross section stranded wire to	50
Cross section stranded with ferrule from	25
Cross section stranded with ferrule to	50
Cross-Section	50
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059

EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
GL test standard	IEC 60947-7-1:2002
Height TS 32	82
Height TS 35/7.5	76.5
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	79
Mounting	TS 35 and TS 32
Number of levels	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	10
Plug gauge acc. EN 60 947-1	B10
Rated Current CSA	150
Rated current CSAus	150
Rated Current IEC	150
Rated Current To UL	150
Rated impulse voltage	8
Rated wire cross section from (AWG)	6
Rated wire cross section to (AWG)	1/0
Rated voltage CSAus	600
Rated Voltage IEC	1000
Rated Voltage To UL	600
Screw size	M 6
Screw type	Hexagon/Allen key
Stripping Length	27
Tariff code	85369010
Torque max	6
Torque Min	3
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	123.6

Width	20
Voltage CSA	600

