# TEST-DISCONNECT TERMINALS PTK

1130.2
Terminal Block Test Disconnect PTK 10sq Beige




- Multi-foot TS35/TS32
- Touch-safe to VBG 4
- Dual function, disconnect & test

## PRODUCT DESCRIPTION

CONTA-CLIP test-disconnect terminals are available in the following three basic versions, each with or without a pre-assembled socket plug. All versions provide touch-safe protection according to DGUV-3. A captive, screw-on sliding partition is used to separate the current and voltage paths. The switch position is always easy to detect since the disconnect screw has a yellow insulating sleeve. In all versions, the STB 14/4 socket plugs can be used for a test pick-off for measuring values using the PS 4 test plug or the conventional (4 mm) insulated test plugs. The VH 19 connecting sleeves and the BS 25 screws or STB 14/4 socket plugs are required for fastening the QVS cross-switches above the terminal block. The cross-switches are available from 2 to 4 poles. The QSB internal cross-switches are positioned within the terminal block and make contact over the sliding contact on the LT- or QT-terminals. The cross-switches are available from 2 to 4 poles. The BS 25 mounting screws are used together with the VH 19 connecting sleeves to establish contact with the QVS cross-switches.

## SPECIFICATIONS

| | |
|---|---|
| Cross-Section | 10 |
| Color | Beige |
| Rated Voltage IEC | 400 |
| Rated Current IEC | 10 |
| Rated impulse voltage | 4 |
| Overvoltage category | III |
| Contamination degree | 3 |
| Approvals | CSA, CSA US |

| | |
|---|---|
| Length | 72 |
| Width | 8 |
| Height TS 35/7.5 | 47 |
| Height TS 32 | 51.5 |

| | |
|---|---|
| Connections | 2 |

| | |
|---|---|
| Number of levels | 1 |
| Plug gauge acc. EN 60 947-1 | A5 |
| Cross connect channels | 2 |
| Cross section single wire from | 0.2 |
| Cross section single wire to | 10 |
| Cross section stranded wire from | 0.2 |
| Cross section stranded wire to | 10 |
| Cross section stranded with ferrule from | 0.2 |
| Cross section stranded with ferrule to | 10 |
| Rated wire cross section from (AWG) | 8 |
| Rated wire cross section to (AWG) | 22 |
| Stripping Length | 12 |
| Screw size | M 4 |
| Torque Min | 1.2 |
| Torque max | 2 |

| | |
|---|---|
| Flamklass | UL94-V2 |
| Operating temperature from | -40 |
| Operating temperature to | 105 |

| | |
|---|---|
| Voltage CSA | 600 |
| Rated Current CSA | 45 |
| CSA test standard | C22.2 No 158 |
| Rated voltage CSAus | 600 |
| Rated current CSAus | 45 |
| CSAus test standard | UL 1059 |

| | |
|---|---|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 24.66 |
| Pack Size | 50 |

