

FEED THROUGH TERMINALS - RK 2.5-240MM²

RK

17370.2

Terminal Block RK 35sq Beige, Fully Enclosed

- Screw in cross connectors
- Material polyamide 6.6 - UL94-V2
- Various colour options
- Temperature resistance -40 °C...+105 °C
- Multi-foot TS35/TS32 options



Product description

Specifications

Approvals	UL, CSA, GL, CSA US, cUL, KEMA KUR, EAC
Color	Beige
Connections	2
Contamination degree	3
Country of origin	CZ
Cross connect channels	1
Cross section single wire from	2.5
Cross section single wire to	50
Cross section stranded wire from	2.5
Cross section stranded wire to	35
Cross section stranded with ferrule from	2.5
Cross section stranded with ferrule to	35
Cross-Section	35
CSA test standard	C22.2 No 158
CSAus test standard	UL 1059
cUL test standard	C22.2 No 158

EAC test standard	TR ZU 004/2011
Flamklass	UL94-V2
GL test standard	IEC 60947-7-1:2002
Height TS 35/7.5	52
Insulation Material	Polyamide 6.6
KEMA KEUR test standard	EN 60947-7-1:2009
Length	58
Mounting	TS 35
Number of levels	1
Operating temperature from	-40
Operating temperature to	105
Overvoltage category	III
Pack Size	20
Plug gauge acc. EN 60 947-1	B9
Rated Current CSA	115
Rated current CSAus	115
Rated Current IEC	125
Rated impulse voltage	8
Rated wire cross section from (AWG)	12
Rated wire cross section to (AWG)	2
Rated voltage CSAus	600
Rated Voltage IEC	800
Screw size	M 6
Screw type	Slotted
Stripping Length	20
Tariff code	85369010
Torque max	5
Torque Min	2.5
Type of terminal	Screw Terminals, DIN Rail terminals
UL test standard	UL 1059
Weight	54.75
Width	16
Voltage CSA	600

