


KUBLER SLIP RING SR085

SR085-25-040411301

SLIP RING 4 SIGNAL / 4 POWER 25MM SHAFT

- Modular system
- Speed max. 800 rpm
- Lifespan 500 million revolutions
- Two-chamber system



Product description

SR085 has a strong design for industrial use. The construction is modular, where load and data signals can be combined individually. The load and data signals take place in physically separated chambers, which guarantees safe operation. The house is built in strong fiberglass-reinforced polycarbonate.

The transmission of load and signal takes place through trailer contacts with double contact surfaces, which are adapted for load or signal. The trailer contacts are asymmetrical to ensure that at least one always has contact, even in the event of vibrations. The load transfer takes place via trailer contacts of copper graphite for high wear resistance. The data transfer trailer connectors are made of copper alloy (gold-plated as an option for low signal voltages). Signal transmission can also be done for field buses e.g. Profibus and CANopen with up to 12 Mbit / s. The number of modules can be up to 20.

Specifications

Contact Resistance Channel	1
Contact Resistance Data Channel	0.1
Dielectric Strength	1000
Hollow Shaft Diameter Max	25
Insulation Resistance	10 ³ MΩ
IP Class	IP50
Power Load Max	25
Speed OF Rotation	800
Temperature range from	-35
Temperature range to	85

Example: Type S8085-25-02-03-11301-V100
(2 data channels, 3 power channels)



Example: Type S8085-25-02-03-11301-V100
(2 data channels, 3 power channels)

