

ADVANCED ILLUMINATION - BL128 EXPANDABLE SERIES

Back Lit Low Profile Backlights

BL128-470C5
AI BL128 470 C5



- Edge to edge back lighting in a 12mm (.48") thick housing
- 2" wide, expandable in 1" increments; Lengths from 1" - 14"
- Optional washdown version offers IP65 compliant design

Product description

The BL128 series is expandable in 1" increments up to 14.4", with optional washdown version that is IP65 compliant. The BL series of compact Backlights provide edge to edge illumination in a 12mm thick housing.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

Specifications

Approvals	IEC 62471, CE, RoHS
Color	Blue
Connector/controller	C5 connector
IP Class	IP64
Length	62
Operating temperature	0°C - 60°C
Photobiological Risk Factor IEC 6247	Group 1 (low risk)
Standard cable length	Up to 2 meters
Wave-Length	470
Width	58.7

