

## ADVANCED ILLUMINATION - BL128 EXPANDABLE SERIES

### Back Lit Low Profile Backlights

BL128-WHIIC  
AI BL128 WHI IC



- Edge to edge back lighting in a 12mm (.48") thick housing
- 2" wide, expandable in 1" increments; Lengths from 1" - 14"
- Optional washdown version offers IP65 compliant design

#### Product description

The BL128 series is expandable in 1" increments up to 14.4", with optional washdown version that is IP65 compliant. The BL series of compact Backlights provide edge to edge illumination in a 12mm thick housing.

#### Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

#### Specifications

|   |                               |
|---|-------------------------------|
| <b>Approvals</b>                            | IEC 62471, CE, RoHS           |
| <b>Color</b>                                | White                         |
| <b>Connector/controller</b>                 | Continuous in-line controller |
| <b>IP Class</b>                             | IP64                          |
| <b>Length</b>                               | 62                            |
| <b>Operating temperature</b>                | 0°C - 60°C                    |
| <b>Photobiological Risk Factor IEC 6247</b> | Group 1 (low risk)            |
| <b>Standard cable length</b>                | Up to 2 meters                |
| <b>Wave-Length</b>                          | WHI                           |
| <b>Width</b>                                | 58.7                          |

