

ADVANCED ILLUMINATION - AL4554 BALA LIGHTING

9" Broad Area Linear Array

AL4554-470IC

Ai BALA Bar Light, 9", Blue, ICS2



- Developed to handle a long wide field with low angle of view
- Very even lighting throughout the area
- Legacy product see AL150

Product description

The AL4554 range of BALA (Broad Area Linear Array) bar lights are legacy part number derived from the AL150 range.

Designed for applications that require broad illumination over a wide area, or for applications requiring an even broader field of illumination, utilise 2 BALA bar lights in parallel.

The AL4554 bar light series is expandable in 1" increments up to 82".

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

Other Wavelength options:

- UV - 395
- Blue - 470
- Green - 520
- Red - 625, 660
- Infrared - 880
- White - WHI

For enquiries or quotes for sizes and power options not listed here please [contact us](#).

Specifications

Approvals	CE, RoHS, IEC
Color	Blue
Connector/controller	Continuous in-line controller
IP Class	IP50
Length	250
Operating temperature	0 - 60°C
Wave-Length	470
Weight	267.6

