## EFFILUX - EFFI-FLEX MODULAR BAR LIGHT

## Adjustable beam angle LED bar

FLEX-5-405-SD-P1 Bar light, 3LED, 135mm,UV 405, semi diffuse, 45°

- Intense and uniform illuminated area
- Continuous or strobe mode
- Full range of colors: from UV to IR, white, tricolor
- Adjustable illumination angles (4 angles) & different projection windows





## Product description

EFFI-Flex is a product that suits your needs with different lens adjustment positions. It 's an adjustable product in terme of wavelength, a compact and easy to install product.

The EFFI-Flex led bars are fitted with high power LED. Through its diffusers (transparent, semi-diffuse and opaline) and polarizers, EFFI-Flex provides a directional, darkfield or diffuse lighting adapted to many machine vision applications.

## Specifications

| Angle of emission          | 45             |
|----------------------------|----------------|
| Approvals                  | CE, RoHS       |
| Central Material           | Aluminium      |
| Color                      | Ultraviolet    |
| Connector/controller       | M12 - 4 pins   |
| IP Class                   | IP50           |
| Length                     | 135            |
| Number of LED              | 5              |
| Operating temperature      | 0°C - 50°C     |
| Optional linescan filter   | Yes            |
| Optional polarising filter | Yes            |
| Supply voltage             | 24             |
| Type of lens               | Semi-diffusive |
| Wave-Length                | 405            |
| Width                      | 51             |
|                            |                |