

EFFILUX - EFFI-FLEX MODULAR BAR LIGHT

Adjustable beam angle LED bar

FLEX-3-RGB-OP-P2

Bar light, 3LED, 95mm, RGB, opaline, 25°



- Intense and uniform illuminated area
- Continuous or strobe mode
- Full range of colors: from UV to IR, white, tricolor
- Adjustable illumination angles (4 angles) & different projection windows

Product description

EFFI-Flex is a product that suits your needs with different lens adjustment positions. It 's an adjustable product in terme of wavelength, a compact and easy to install product.

The EFFI-Flex led bars are fitted with high power LED. Through its diffusers (transparent, semi-diffuse and opaline) and polarizers, EFFI-Flex provides a directional, darkfield or diffuse lighting adapted to many machine vision applications.

Specifications

| | |
|-----------------------------------|--------------|
| Angle of emission | 25 |
| Approvals | CE, RoHS |
| Central Material | Aluminium |
| Color | RGB |
| Connector/controller | M12 - 4 pins |
| IP Class | IP50 |
| Length | 95 |
| Number of LED | 3 |
| Operating temperature | 0°C - 50°C |
| Optional linescan filter | Yes |
| Optional polarising filter | Yes |
| Supply voltage | 24 |
| Type of lens | Opaline |
| Wave-Length | RGB |
| Width | 51 |