

EFFILUX - EFFI-SMART LED BAR LIGHT

Double row LED bar light

SMART-12-405-OP-P2

2 row bar light, 12 LED, UV 405, opaline, 25°

- Chainable: Double I/O connectors
- Auto-strobe
- Built in driver
- Waterproof (IP67)



Product description

The EFFI-SMART is a dual row high power LED bar light, with a choice of 3 diffuser plates (clear, semi-diffuse, diffuse) so the user can create a suitable balance between power and homogeneity.

Integrated controller for dimming or auto-strobe functionality, offering 700% increased intensity in strobe mode as compared to continuous operation. To overcome challenging working environments the EFFI-SMART has a robust design with IP67 rating.

The highly flexible design allows users to easily adjust lens positioning and diffuser plates when necessary.

Other wavelengths and lengths available, [contact us](#) for more information.

Specifications

| | |
|----------------------------|--|
| Angle of emission | 25 |
| Approvals | CE, RoHS |
| Central Material | Aluminium |
| Color | Ultraviolet |
| Connector/controller | 2 x M12 5 contacts (1 male & 1 female) |
| IP Class | IP67 |
| Length | 116 |
| Number of LED | 12 |
| Operating temperature | 0°C - 45°C |
| Optional linescan filter | Yes |
| Optional polarising filter | Yes |
| Supply voltage | 24 |
| Type of lens | Opaline |
| Wave-Length | 405 |
| Width | 70 |