

ADVANCED ILLUMINATION - LL174 LINEAR LIGHTING

Expandable High Power Lighting

LL174-365I3

LL174 bar light, 6", UV 365, strobe/continuous controller



- Developed for large areas or Line scan applications
- Available in increments of 152 mm (6 inches) up to 1 219 mm (48 inches)

Product description

The LL174 is a high intensity bar light with a large degree of customisation. Available in 16 wavelengths, expandable up to 84" in 6" increments.

There is optional heat sink for higher performance and/or high ambient temperature.

3 different lens options are also available, arrow, medium and wide beam spreads.

Power options include:

- C1 connector - for use with DCS series controllers
- C5 connector - for use with Pulsar 320 strobe controller
- Continuous in-line controller - powered by 24V power supply
- Combination strobe/continuous in-line controller - powered by 24V power supply
- Default-OFF strobe/continuous in-line controller - powered by 24V power supply
- Flying/tinned leads - powered by 24V power supply

All Wavelength options:

- UV - 365, 375, 385, 395
- Violet - 405
- Royal blue - 455
- Blue - 470
- Cyan - 505
- Green - 530
- Amber - 590
- Red orange - 625
- Red - 660
- Infrared - 730, 850, 940
- White - WHI


For enquiries or quotes for sizes and power options not listed here please [contact us](#).

Specifications

Approvals	IEC 62471, CE, RoHS
Color	Ultraviolet
Connector/controller	Strobe/continuous in-line controller
IP Class	IP65

Length	174
Operating temperature	0°C - 60°C
Photobiological Risk Factor IEC 6247	Group 2 (moderate risk)
Standard cable length	Up to 2 meters
Wave-Length	365
Weight	195.1
Width	34

UNIT NUMBER	NEW SKALD	SKALD
U174	172.7 (6.81)	174.0 (6.85)
U17412	326.1 (12.84)	329.2 (12.96)
U17418	478.6 (18.84)	481.7 (18.96)
U17430	783.4 (29.84)	786.5 (30.16)
U17436	935.8 (34.84)	938.9 (35.00)
U17442	1088.2 (40.84)	1091.3 (42.96)
U17448	1240.6 (45.84)	1243.7 (48.96)
U17454	1393.0 (50.84)	1396.1 (51.96)
U17460	1545.4 (55.84)	1548.5 (56.96)
U17466	1697.8 (60.84)	1700.9 (61.96)
U17472	1850.2 (65.84)	1853.3 (66.96)
U17478	2002.6 (70.84)	2005.7 (71.96)
U17484	2155.0 (75.84)	2158.1 (76.96)
UNIT IN R.M.H (INC-415)		



UNIT NUMBER	NEW SKALD	SKALD
U174	172.7 (6.81)	174.0 (6.85)
U17412	326.1 (12.84)	329.2 (12.96)
U17418	478.6 (18.84)	481.7 (18.96)
U17430	783.4 (29.84)	786.5 (30.16)
U17436	935.8 (34.84)	938.9 (35.00)
U17442	1088.2 (40.84)	1091.3 (42.96)
U17448	1240.6 (45.84)	1243.7 (48.96)
U17454	1393.0 (50.84)	1396.1 (51.96)
U17460	1545.4 (55.84)	1548.5 (56.96)
U17466	1697.8 (60.84)	1700.9 (61.96)
U17472	1850.2 (65.84)	1853.3 (66.96)
U17478	2002.6 (70.84)	2005.7 (71.96)
U17484	2155.0 (75.84)	2158.1 (76.96)
UNIT IN R.M.H (INC-415)		

