
## EFFILUX - LINE3 - POWERFUL LED LINE LIGHT

Effilux - Line3

EFFI-LINE32200-625

EFFI-LINE3-2200-625 - Length: 2200mm, Color: Red



- IP5X (dust protected) / IP67 version available
- Operation environment Temperature: 0°C to 50°C -Humidity: 20 to 85%RH (with no condensation) - Altitude: Up to 2000m



## Product description

EFFI-Line3 is the new generation of LED line light intended for linescan applications designed and manufactured by Effilux.

The light has all the requested qualities for this type of application as a large homogeneity, very high power and an excellent collimation.

- Versatility. Efficient over a wide range of working distances with scalable power and homogeneity according to the needs.
- Built-in driver for continuous mode or strobe mode, with analog intensity control (AIC) allowing to adjust the output power.

Robust design for inspection in rough environments.

What applications can I use line light for?

EFFILUX high uniformity LED line lights can be used in conjunction with line scan cameras for line scan inspection application such as:

- Web inspections (such as films, paper, cotton, textiles)
- Sorting & packaging (such as refuse, postal mail, foodstuffs, packaging)
- Transport-related applications (such as underfloor, rail, overhead line, and container inspections)
- Large area continuous web applications: paper, textiles, wood, etc
- High speed inspections for printing industry
- Code reading: QR codes, barcodes, etc. Inspection of transparent and/or reflective objects: film, glass, metal, coated surface, solar panels.
- Inspection of transparent and/or reflective objects: film, glass, metal, coated surface, solar panels

## About EFFILUX -

EFFILUX designs and manufactures powerful technical LED lighting systems for machine vision, quality control, scientific imaging, biomedical and any optical measuring device.

Effilux has used all its expertise and its 13 years of experience in the field of machine vision to design a versatile and easy-to-use light that has all the qualities required for linear applications.

With machine vision LED lighting designed to easily adapt in the field and highly robust in design, EFFILUX are revolutionising with their interchangeable lens and filter solutions.

Do you think your application could benefit from these new LED line lights?

Find out more by emailing vision@oem.co.uk or calling 01162849900

## Specifications

Approvals	CE, UKCA, REACH, RoHS
Central Material	Aluminium

Color	Red
Connector/controller	M12, 4P
IP Class	IP5X
Length	2200
Operating temperature	0-50°C
Standard cable length	500mm
Supply voltage	24
Wave-Length	625
Width	52

