

ADVANCED ILLUMINATION - BL-S050075 EUROBRITE™

Strobe /Continuous Backlight

BL-S050075-625
Ai EuroBrite™ Backlight, Small, Red



- Cost-effective, feature-rich design
- On-board smart driver - seamless strobe or continuous
- Robust, sealed IP67 enclosure
- Easy M12X1 connection



Product description

With complete built in control for continuous and strobe modes, the Eurobrite™ range outdoes the competition in many ways. One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.


Additional features:

- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please [contact us](#).


Specifications

Approvals	IEC 62471, CE, RoHS
Color	Red orange
Connector/controller	Strobe
IP Class	IP67
Length	75
Operating temperature	0°C - 60°C
Photobiological Risk Factor IEC 6247	Group 1 (low risk)
Standard cable length	No cable included, use standard coded 5-pin M12
Wave-Length	625
Weight	92.53
Width	89



Length (mm)	75
Width (mm)	89
Height (mm)	30

Dimensions are in millimeters



Length (mm)	75
Width (mm)	89
Height (mm)	30

Dimensions are in millimeters