

ADVANCED ILLUMINATION - BL-S100150 EUROBRITE™

Strobe/Continuous Backlight

BL-S100150-470
Ai EuroBrite™ Backlight, Medium, Blue



- Double the size of the BL-S050075
- Cost-effective, feature-rich design
- On-board smart driver - seamless strobe or continuous
- IP67 enclosure

Product description

With complete built-in control for continuous and strobe modes, the Eurobrite™ range outdoes the competition in many ways. One major feature of the Eurobrite™ is Adaptive Power™ which utilizes an onboard thermistor to maximize light output in continuous mode. As well as Adaptive Power™ to provide maximal output pulse in strobe mode regardless of the exposure period.


Additional features:

- IP67 sealed enclosure suitable for washdown environments
- Rugged construction that has been tested to withstand over 1000lb
- Industrial grade LEDs providing high-intensity surface illumination of 38klux

For other wavelength options not listed here please [contact us](#).


Specifications

| | |
|---|---|
| Approvals | IEC 62471, CE, RoHS |
| Color | Blue |
| Connector/controller | Strobe |
| IP Class | IP67 |
| Length | 150 |
| Operating temperature | 0°C - 60°C |
| Photobiological Risk Factor IEC 6247 | Group 1 (low risk) |
| Standard cable length | No cable included, use standard coded 5-pin M12 |
| Wave-Length | 470 |
| Weight | 254.1 |
| Width | 139 |



| | |
|-------------|-----|
| Length (mm) | 150 |
| Width (mm) | 139 |
| Height (mm) | 30 |

Dimensions are in millimeters



| | |
|-------------|-----|
| Length (mm) | 150 |
| Width (mm) | 139 |
| Height (mm) | 30 |

Dimensions are in millimeters