ASCO - COAXIAL VALVES

SCG287A001



- G3/8 G1
- \bullet Temperature -20 to 100 $^{\circ}$ C
- Pressure 0 to 40 bar
- Medium water, oil, gases
- Brass or stainless steel body



Product description

Coaxial valves are used in applications for high pressure and high flows. The coaxial valve can accommodate flow in both directions. Coaxial valves are available in electrically controlled versions and pressure controlled namur versions.

Model SCG287 Function



- - 2/2 normally closed/open
 - 3/8"-1"
 - 0-40 bar
 - 37-2,031 l/min.

• Brass/stainless

Model SCG387	Function
	Brass/stainless
	• 3/2 normally closed/open
	• 3/8"-1"
	• 0-40 bar
	• 37-203 l/min.

Model G287/Namur	Function
	 Brass/stainless 2/2 normally closed/open 3/8"-1" 0-40 bar 37-203 l/min.

 Brass/stainless 3/2 normally closed/open 3/8"-1" 	Model G387/Namur	Function
• 3/8"-1"		Brass/stainless
		 3/2 normally closed/open
0.404		• 3/8"-1"
● 0-40 bar		• 0-40 bar
• 37-203 l/min.		• 37-203 l/min.

For more information contact OEM Automatic, product area Pressure & Flow and order a separate catalogue.

Specifications

Connection Thread	3/8 BSP
Commodation Timedu	0/0 001
Differential Pressure Air Max	40
Differential Pressure Max	40
Differential Pressure Min	0
Differential Pressure Oil Max	40
Differential Pressure Water Max	40
Flow Max I/min Double	36.6
Function 1	2/2
Function 1 Function 2	2/2 Normally Closed
Function 2	Normally Closed
Function 2 Material Body	Normally Closed Brass
Function 2 Material Body Temperature range of media from	Normally Closed Brass -20