



# ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D002  
Solenoid valve 2/2 NC 1/2" 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m3/h



## Product description

## Specifications

Coil Material	Epoxy
Connection Thread	1/2 BSP
Differential Pressure Air Max	14
Differential Pressure Max	14
Differential Pressure Min	0.35
Differential Pressure Oil Max	10
Differential Pressure Water Max	10
Flow Factor / Flow Coefficient	3,4
Flow Max l/min Double	57
Function 1	2/2
Function 2	Normally Closed (SPST)
Material Body	Brass
Material of seals	NBR
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass

<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	20
<b>Membrane Material</b>	NBR
<b>Power Consumption</b>	6
<b>Response Closing</b>	15
<b>Response From Stroke</b>	60
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	85
<b>Temperature range to</b>	75
<b>Throughput</b>	16
<b>Type of valve</b>	Solenoid valve
<b>Weight</b>	0.8
<b>Viscosity Max</b>	65
<b>Voltage AC</b>	230

