



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D009
Solenoid valve 2/2 NC 3/4 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m3/h



Product description

Specifications

Coil Material	Epoxy
Connection Thread	3/4 BSP
Differential Pressure Air Max	9
Differential Pressure Max	9
Differential Pressure Min	0.35
Differential Pressure Oil Max	9
Differential Pressure Water Max	9
Flow Factor / Flow Coefficient	4,3
Flow Max l/min Double	72
Function 1	2/2
Function 2	Normally Closed (SPST)
Material Body	Brass
Material of seals	NBR
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass

Materials Spring	Stainless steel
Max. pressure	20
Membrane Material	NBR
Power Consumption	6
Response Closing	15
Response From Stroke	60
Temperature range from	-20
Temperature range of media from	-20
Temperature range of media to	85
Temperature range to	75
Throughput	19
Type of valve	Solenoid valve
Weight	0.8
Viscosity Max	65
Voltage AC	230

