



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D014
Solenoid valve 2/2 NO 1" 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m3/h



Product description

Specifications

Coil Material	Epoxy
Connection Thread	G1
Differential Pressure Air Max	9
Differential Pressure Max	9
Differential Pressure Min	0.35
Differential Pressure Oil Max	9
Differential Pressure Water Max	9
Flow Factor / Flow Coefficient	11,1
Flow Max l/min Double	185
Function 1	2/2
Function 2	Normally open (SPST)
Material Body	Brass
Material of seals	NBR
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass

Materials Spring	Stainless steel
Max. pressure	18
Membrane Material	NBR
Power Consumption	15.4
Response Closing	40
Response From Stroke	120
Temperature range from	-20
Temperature range of media from	-20
Temperature range of media to	85
Temperature range to	75
Throughput	25
Type of valve	Solenoid valve
Weight	2.1
Viscosity Max	65
Voltage AC	230

