

ASCO - 2/2 SERVO-CONTROLLED 1/4"-3/4"

SCB223A125

Solenoid valve 2/2 NC 1/4" 230/50

- Normally closed
- For high pressure
- Standard working pressure 0.7 bar to 100 bar
- Housing in brass or stainless



Product description

Specifications

Coil Material	Epoxy
Connection Thread	1/4 BSP
Differential Pressure Air Max	100
Differential Pressure Max	100
Differential Pressure Min	0.7
Differential Pressure Oil Max	100
Differential Pressure Water Max	100
Flow Factor / Flow Coefficient	1,3
Flow Max l/min Double	21.7
Function 1	2/2
Function 2	Normally Closed
IP Class	IP65
Material Body	Brass
Material Bolt	Stainless steel
Material of seals	NBR
Material Plunger	Stainless steel

Material Short Call	Copper
Material Slide Ring	PTFE
Materials Piston Seal	PTFE
Materials Seat	Brass
Materials Seat Seal	Urethane
Max. pressure	100
Power Consumption	16.7
Response Closing	15
Response From Stroke	60
Temperature range from	-20
Temperature range of media from	-20
Temperature range of media to	90
Temperature range to	50
Throughput	8
Type of valve	Solenoid valve
Weight	0.7
Viscosity Max	65
Voltage AC	230

