



**ASCO - 2/2 SERVO-CONTROLLED 1/4"-  
3/4"**

SCB223B005  
Solenoid valve 2/2 NC 3/4" 230/50

- Normally closed
- For high pressure
- Standard working pressure 0.7 bar to 100 bar
- Housing in brass or stainless



Product description

Specifications

Coil Material	Epoxy
Connection Thread	3/4 BSP
Differential Pressure Air Max	50
Differential Pressure Max	50
Differential Pressure Min	1.8
Differential Pressure Oil Max	50
Differential Pressure Water Max	50
Flow Factor / Flow Coefficient	6,7
Flow Max l/min Double	112
Function 1	2/2
Function 2	Normally Closed (SPST)
IP Class	IP65
Material Body	Brass
Material Bolt	Stainless steel
Material of seals	NBR
Material Plunger	Stainless steel

<b>Material Short Call</b>	Copper
<b>Material Slide Ring</b>	PTFE
<b>Materials Piston Seal</b>	PTFE
<b>Materials Seat</b>	Brass
<b>Materials Seat Seal</b>	Urethane
<b>Max. pressure</b>	100
<b>Power Consumption</b>	16.7
<b>Response Closing</b>	15
<b>Response From Stroke</b>	60
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	90
<b>Temperature range to</b>	50
<b>Throughput</b>	19
<b>Type of valve</b>	Solenoid valve
<b>Weight</b>	1.5
<b>Viscosity Max</b>	65
<b>Voltage AC</b>	230

