

ASCO - 2/2 ANGLE-SEAT VALVE AIR  
CONTROLLED 3/8"-3/4"

E290A791VI  
Angle seat valve 3/8" NC "MINI"

- Normally closed, normally open
- Extremely compact version
- Working pressure 0 bar to 16 bar
- Housing in stainless



Product description

Specifications

Connection Air	1/8 BSP
Connection Thread	3/8 BSP
Differential Pressure Air Max	16
Differential Pressure Max	16
Differential Pressure Min	0
Differential Pressure Oil Max	16
Differential Pressure Water Max	16
Differential steam pressure max	10
Flow Factor / Flow Coefficient	2,8
Flow Max l/min Double	47
Function 1	2/2
Function 2	Normally Closed
Material Body	Stainless steel 316L
Material of body	Stainless steel 316L
Material of seals	PTFE
Material Operator	Fiberglass reinforced polyamide

Material Rod	Stainless steel
Materials Avskrapningstätning	FPM
Materials Gland	PTFE
Materials Piston Rod Seal	Stainless steel 303
Materials Piston Seal	PTFE
Max. pressure	16
Packing Materials	Stainless steel
Pilot Pressure Max	10
Pilot Pressure Min	4
Temperature range from	-10
Temperature range of media from	-10
Temperature range of media to	184
Temperature range to	60
Throughput	10
Weight	0.35
Viscosity Max	600

