## ASCO - 2/2 ANGLE-SEAT VALVE AIR CONTROLLED 3/8"-3/4"

E290A792VI Angle seat valve 1/2 NC MINI

- Normally closed, normally open
- Extremely compact version
- Working pressure 0 bar to 16 bar
- Housing in stainless



Product description

Specifications

Connection Air	1/8 BSP
Connection Thread	1/2 BSP
Differential Pressure Air Max	12
Differential Pressure Max	12
Differential Pressure Min	0
Differential Pressure Oil Max	12
Differential Pressure Water Max	12
Differential steam pressure max	10
Flow Factor / Flow Coefficient	4,1
Flow Max I/min Double	68
Function 1	2/2
Function 2	Normally Closed (SPST)
Material Body	Stainless steel 316L
Material of seals	PTFE
Material Operator	Fiberglass reinforced polyamide
Material Rod	Stainless steel

## 

Materials Avskrapningstätning	FPM
Materials Gland	PTFE
Materials Piston Rod Seal	Stainless steel 303
Materials Piston Seal	PTFE
Max. pressure	16
Packing Materials	Stainless steel
Pilot Pressure Max	10
Pilot Pressure Min	4
Temperature range from	-10
Temperature range of media from	-10
Temperature range of media to	184
Temperature range to	60
Throughput	15
Weight	0.4
Viscosity Max	600

