



ASCO - 3/2 SEAT VALVE AIR CONTROLLED 1/2"-2"

E398A004
Angle seat valve 1.1/4" 3/2 Universal

- Universal
- Working pressure 0 to 40 bar
- For temperatures up to +250 °C
- For viscosity up to 5,000 cSt




Product description


Specifications

Approvals	SIL2
Connection Air	1/4 BSP
Connection Thread	1 1/4 BSP
Differential Pressure Air Max	40
Differential Pressure Max	40
Differential Pressure Min	0
Differential Pressure Oil Max	40
Differential Pressure Water Max	40
Differential steam pressure max	40
Function 1	3/2
Function 2	Universal
Material Body	Stainless steel 316L
Material of seals	Graphite
Material Operator	Nickel plated aluminum
Material Rod	Stainless steel
Materials Gland	PTFE flask filled

Materials Piston Seal	Bronze, PTFE
Max. pressure	40
Packing Materials	Stainless steel
Pilot Pressure Max	10
Temperature range from	-25
Temperature range of media from	-10
Temperature range of media to	250
Temperature range to	180
Throughput	32
Type of valve	Seat valve
Weight	9.38
Viscosity Max	5000



Ventil (ØAA)	ØA	ØB	C	D	E	G	ØH	ØP	Q
1/2"	15	110	203,1	151,6	85	1/8	33	95	51,5
3/4"	20	132,5	229,2	170,9	110	1/8	40	117	58,3
1"	25	132,5	244,9	180,9	120	1/8	46	117	64
1 1/4"	32	191	318,2	237,2	145	1/4	57	172,5	81
1 1/2"	40	191	361,7	259,2	150	1/4	65	172,5	102,5
2"	50	247	436	328,5	190	1/4	75	230	107,5



Ventil (ØAA)	ØA	ØB	C	D	E	G	ØH	ØP	Q
1/2"	15	110	203,1	151,6	85	1/8	33	95	51,5
3/4"	20	132,5	229,2	170,9	110	1/8	40	117	58,3
1"	25	132,5	244,9	180,9	120	1/8	46	117	64
1 1/4"	32	191	318,2	237,2	145	1/4	57	172,5	81
1 1/2"	40	191	361,7	259,2	150	1/4	65	172,5	102,5
2"	50	247	436	328,5	190	1/4	75	230	107,5