

ASCO - 2/2 STEAM VALVE 3/8"-3/4"

SCE222D002  
Solenoid valve 2/2 NC 1/2" 230/50

- Normally closed
- Media temperature up to +180 °C
- Working pressure 0 to 9 bar steam
- Housing in brass



Product description

Specifications

Coil Material	Epoxy
Connection Thread	1/2 BSP
Differential Pressure Max	9
Differential Pressure Min	0
Flow Factor / Flow Coefficient	3,3
Flow Max l/min Double	55
Function 1	2/2
Function 2	Normally Closed (SPST)
IP Class	IP65
Material Body	Brass
Material Bolt	Brass
Material of seals	PTFE
Material piston ring	PTFE flask filled
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass

<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	10
<b>Power Consumption</b>	16.7
<b>Response Closing</b>	75
<b>Response From Stroke</b>	100
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	184
<b>Temperature range to</b>	40
<b>Throughput</b>	16
<b>Type of valve</b>	Solenoid valve
<b>Weight</b>	1.3
<b>Voltage AC</b>	230

