

ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220027  
Solenoid valve 2/2 NC 1 1/4" 230VAC



- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



Product description

Specifications

Coil Material	Epoxy
Connection Thread	1 1/4 BSP
Differential Pressure Air Max	10
Differential Pressure Max	10
Differential Pressure Min	0.35
Differential Pressure Water Max	10
Flow Max l/min Double	213
Function 1	2/2
Function 2	Normally Closed (SPST)
IP Class	IP65
Material Body	Brass
Material of seals	EPDM
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass
Materials Seat Seal	PTFE

<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	10
<b>Power Consumption</b>	10.5
<b>Response Closing</b>	40
<b>Response From Stroke</b>	120
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	184
<b>Temperature range to</b>	40
<b>Throughput</b>	28
<b>Type of valve</b>	Solenoid valve
<b>Voltage AC</b>	230

