

ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220031  
Solenoid valve 2/2 NC 2" 230VAC



- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



Product description

Specifications

Coil Material	Epoxy
Connection Thread	G2
Differential Pressure Air Max	10
Differential Pressure Max	10
Differential Pressure Min	0.35
Differential Pressure Water Max	10
Flow Max l/min Double	617
Function 1	2/2
Function 2	Normally Closed (SPST)
IP Class	IP65
Material Body	Brass
Material of seals	EPDM
Material Plunger	Stainless steel
Material Short Call	Copper
Materials Seat	Brass
Materials Seat Seal	PTFE

<b>Materials Spring</b>	Stainless steel
<b>Max. pressure</b>	10
<b>Power Consumption</b>	10.5
<b>Response Closing</b>	40
<b>Response From Stroke</b>	120
<b>Temperature range from</b>	-20
<b>Temperature range of media from</b>	-20
<b>Temperature range of media to</b>	184
<b>Temperature range to</b>	40
<b>Throughput</b>	44
<b>Type of valve</b>	Solenoid valve
<b>Voltage AC</b>	230

