ASCO - 2/2 PROPORTIONAL VALVE 1/4"

SCB202A012VS3 Proportional valve 2/2 NC 1/4" 24VDC



- Normally closed
- Compact version
- Working pressure 0 to 16 bar
- Housing in brass or stainless



Product description

Specifications

Coil Material	Ероху
Connection Thread	1/4 NPT
Differential Pressure Air Max	8
Differential Pressure Min	0
Differential pressure vacuum max	1
Flow Factor / Flow Coefficient	0,12
Flow Max I/min Double	2
Function 1	2/2
Function 2	Normally Closed (SPST)
Function 2 IP Class	Normally Closed (SPST) IP65
IP Class	IP65
IP Class Material Body	IP65 Stainless steel 303
IP Class Material Body Material Plunger	IP65 Stainless steel 303 Stainless steel
IP Class Material Body Material Plunger Material Slide Ring	IP65 Stainless steel 303 Stainless steel PTFE
IP Class Material Body Material Plunger Material Slide Ring Materials Seat	IP65 Stainless steel 303 Stainless steel PTFE Stainless steel

Max. pressure	35
Power Consumption	8
Sensitivity	<2%
Temperature range from	-10
Temperature range of media from	-10
Temperature range of media to	90
Temperature range to	75
Throughput	2.4
Weight	0.6
Viscosity Max	21
Voltage DC	24

