## ASCO - FLOWTRONIC D PROGRAMMABLE PROPORTIONAL VALVE FOR FLOW REGULATION

60701017 Flowtronic,G1/4",500NI,4-20mA + displ.

- · Direct operating
- Rapid and accurate pressure regulation
- Simple optimisation of regulation parameters
- LED display



## Product description

Flowtronic<sup>D</sup>, with its direct operating solenoid regulates flow with high accuracy and short response time. The regulation parameters can be easily adjusted via a PC allowing the regulator to be set optimally for each individual application. Flowtronic<sup>D</sup> can, naturally, be used without software; flow is then set using push buttons on the regulator operation panel. The regulator has auto-tune, which automatically regulates the current to the coil for optimal regulation, as well as fault indication via LEDs on the control panel. Available with or without a display.

## Connection



Pin	Description	Cable 2 m (5 wires)	Cable 5 m (6 wires)
1	Supply 24 V DC	brown	brown
2	Analogue signal, input	white	white
3	Earth, supply	blue	green
	Earth, analogue control signal*		yellow
4	Analogue signal, output	black	pink
5	Digital output (pressure switch)	grey	grey
Housing	Screening (EMC)	screen	screen

## Specifications



Connection Thread	G1/4
Flow Max I/min Double	500
IP Class	IP65
Load Max	1250
Material of body	Aluminium
Material of seals	NBR
Materials Internal Parts	Aluminium, Brass, Stainless steel
Max. pressure	8
Power Consumption	30
Response Time	200
Temperature range from	0
Temperature range of media from	0
Temperature range of media to	50
Temperature range to	40
Throughput	5
Weight	1.85
Voltage DC	24

