



ASCO - COAXIAL VALVES




SCG287A014

- G3/8 - G1
- Temperature -20 to 100 ° C
- Pressure 0 to 40 bar
- Medium water, oil, gases
- Brass or stainless steel body



Product description

Coaxial valves are used in applications for high pressure and high flows. The coaxial valve can accomodate flow in both dircetions. Coaxial valves are available in electrically controlled versions and pressure controlled namur versions.

Model SCG287	Function
	<ul style="list-style-type: none">• Brass/stainless• 2/2 normally closed/open• 3/8"-1"• 0-40 bar• 37-2,031 l/min.
Model SCG387	Function
	<ul style="list-style-type: none">• Brass/stainless• 3/2 normally closed/open• 3/8"-1"• 0-40 bar• 37-203 l/min.
Model G287/Namur	Function
	<ul style="list-style-type: none">• Brass/stainless• 2/2 normally closed/open• 3/8"-1"• 0-40 bar• 37-203 l/min.

Model G387/Namur**Function**

- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

For more information contact OEM Automatic, product area Pressure & Flow and order a separate catalogue.

Specifications

Connection Thread	1/2 BSP
Differential Pressure Air Max	40
Differential Pressure Min	0
Differential Pressure Oil Max	40
Differential Pressure Water Max	40
Flow Max l/min Double	86.6
Function 1	2/2
Function 2	Normally open (SPST)
Material Body	Stainless steel
Temperature range of media from	-20
Temperature range of media to	100
Throughput	15
Voltage AC	230