

BANICO GAS SOLENOID VALVE ZEV SERIES

ZEV10

ZEV, 3/8BSP, 360, 2-way, Normally Closed

- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



Product description

Fast Acting Design with max pressure to 360 mbar. Automatic gas solenoid valves are used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas. Two way normally closed design. Fitted with 1/4" plug ports for pressure gauge and fitting to proving and interlock system. Available in sizes from 3/8" to 3" in Automatic (up to 8" in Flanged)

Specifications

| | |
|--|---------------------------|
| Cable Entry | PG11 Live, Neutral, Earth |
| Connection Thread | 3/8 BSP |
| Function | 2-way, Normally Closed |
| Height | 112 |
| IP Class | IP54 |
| Length | 72 |
| Material Body | Die cast aluminium |
| Material of filter | Stainless steel 303 |
| Material of seals | NBR |
| Materials Spring | Stainless Steel 302 |
| Max number of operations per minute | 20 |
| Max. pressure | 360 |

| | |
|---------------------------------|-----------|
| Power Consumption | 15 |
| Response time | <1 second |
| Temperature ambient from | -15 |
| Temperature ambient to | 60 |
| Weight | 1.1 |
| Voltage AC | 230 |