
## **KUEBLER - INCREMENTAL ENCODER MINIATURE SERIES 2400/2420**

2400.1122.0050 Encoder Inc. P/P, radial cable, 5-24VDC



- House diameter Ø24 mm
- Cable connection 2 metres
- Miniature version.
- Temperature compensation



Kiibler

#### Product description

Model 2400/2420 is a pulse generator series for industrial applications for confined spaces or where the sensor needs to be lightweight. The models 2400/2420 have a so-called Push-Pull output which means that it can be connected to an input that is either PNP or NPN. Output signals are A, B, 0. They also have inverted signals to be connected to inputs that are adapted for malfunction.

Please refer to the images below for ordering information.

Order code Shaft version Type		
1 = φ 24 mm [0.94"] 3 = φ 28 mm [1.10"] 2 = φ 30 mm [1.18"]  5 Shaft (φ x L) 1 = φ 4 x 10 mm [0.16 x 0.39"] 3 = φ 5 x 10 mm [0.20 x 0.39"], with flat 2 = φ 6 x 10 mm [0.24 x 0.39"] 4 = φ 1/4" x 10 mm [1/4" x 0.39"], with flat 1) 6 = φ 6 x 10 mm [0.24 x 0.39"], with flat 1)	Output circuit / power supply  1 = push-pull (without inverted signal) / 5 24 V DC  2 = push-pull (with inverted signal) / 5 24 V DC  3 = push-pull (without inverted signal) / 8 30 V DC  4 = push-pull (with inverted signal) / 8 30 V DC  Type of connection  1 = axial cable, 2 m [6.56] PVC  A = axial cable, 2 m [6.56] PVC  B = radial cable, 2 m [6.56] PVC  B = radial cable, special length PVC *)  *) Available special length PVC *)  *) Available special lengths (connection types A, B):  3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21]  order code expansion .XXXX = length in dm  ex.: 05.2400.122A.1024.0030 (for cable length 3 m)	Pulse rate 4, 6, 8, 10, 16, 20, 25, 36, 40, 50, 60, 80, 100, 120, 125, 180, 200, 250, 300, 360, 400, 500, 512, 1000, 1024 (e.g. 360 pulses => 0360)  Stock types 05.2400.1122.0050 05.2400.1122.0360 05.2400.1122.0500 05.2400.1122.1000 05.2400.1122.1024  Optional on request - other pulse rates

## Order code Hollow shaft



# 6 Flange

1 = ø 24 mm [0.94"]

Blind hollow shaft
(insertion depth max. 14 mm [0.55"])

1 - a 4 mm [0.16"]

1 = ø 4 mm [0.16"] 2 = ø 6 mm [0.24"]

 $4 = 0.01/4''^{-1}$ 

Output circuit / power supply

- 1 = push-pull (without inverted signal) / 5 ... 24 V DC
- 2 = push-pull (with inverted signal) / 5 ... 24 V DC
- 3 = push-pull (without inverted signal) / 8 ... 30 V DC
- 4 = push-pull (with inverted signal) / 8 ... 30 V DC

#### Type of connection

1 = axial cable, 2 m [6.56'] PVC

- A = axial cable, special length PVC \*)
- 2 = radial cable, 2 m [6.56'] PVC
- B = radial cable, special length PVC \*)
- \*) Available special lengths (connection types A, B): 3, 5, 8, 10, 15 m [9.84, 16.40, 26.25, 32.80, 49.21'] order code expansion .XXXX = length in dm ex.: 05.2420.122A.1024.0030 (for cable length 3 m)

### Pulse rate

4, 6, 8, 10, 16, 20, 25, 36, 40, 50, 60, 80, 100, 120, 125, 180, 200, 250, 300, 360, 400, 500, 512, 1000, 1024 (e.g. 360 pulses => 0360)


Stock types 05.2420.1212.0500 05.2420.1222.0500 05.2420.1222.1000 05.2420.1222.1024

#### Optional on request


- other pulse rates

#### Specifications


Connection Thread	Cable
Housing diametre	24
IP Class	IP50
Mounting	Shoulder
Output	Push/Pull
Pulse Max	5000
Resolution	50 pulses/turn
Sensor type	Incremental
Sensor type Shaft Diameter	Incremental 4
Shaft Diameter	4
Shaft Diameter Supply Voltage DC Max	30
Shaft Diameter Supply Voltage DC Max Supply Voltage DC Min	4 30 5











+UB manöverspänning
OV manöverspänning
Kanal A
(Kanal Ä)
Kanal B
(Kanal B)
Kanal O
(Kanal D)
Var none med att ALTID isole

Var noga med att ALLTID isoler oanvända kablar innan givaren