## IDEM HLM-CBA/HLM-SS-CBA TAPE CONVERGENCE SENSOR EXPLOSION PROOF

175463 HLM-SS-CBA-EX switch c/w SS Roller 1NC 1NO

- Explosion proof
- 2 types of lever rollers
- Perfect for smaller conveyors
- Small dimensions
- Different contact configurations





## Product description

The offer of tape cone detectors in the Mini IDEM version complements a wide range of cable switches used for emergency stop along conveyors. They are mounted along the conveyor belt and indicate the crookedness of the conveyor belt. We offer standard models (casting made of metal) and made of stainless steel. The rollers of these breakers can be of plastic or stainless steel.

## Specifications

| Actuator                    | Stainless steel roller  |
|-----------------------------|---|
| Approvals                   | ISO 14119, EN60947-5-1, EN60204-1, ISO 13849-1, EN62061, UL 508 |
| Atex approved               | Yes   |
| Cable length                | 3 m   |
| Central Material            | Stainless steel 316   |
| Conduit entry               | 3m 4 core Ex  |
| Contacts                    | 1NC 1NO   |
| Integrated LED indication   | No  |
| IP Class                    | IP69K   |
| Lifespan Electrical         | 100,000 cycle min. (at full load)                               |
| Mechanical reliability B10d | 500,000 operations at 100mA load                                |
| Minimum current             | 5V 5mA DC   |
| Mounting                    | 4 x M5  |
| Operating temperature       | -20°C+60°C  |

| Rated insulation voltage | 300 V AC                 |
|--------------------------|--------------------------|
| Thermal current (Ith)    | 10                       |
| Utilisation category     | AC15                     |
| Vibration                | IEC68-2-6 10-55Hz 0.35mm |
| Withstand voltage        | 2500 V AC                |

