

DATALOGIC POWERSCAN PBT/PM9100

PM9100-433RB

PowerScan PM9100, 433 MHz, Linear Imager,
Removable Battery

- Detects 1D code types
- Reads up to 2.5 mils codes
- 60,000+ reads per charge
- Interfaces: keyboard wedge, RS-232, USB



Product description

Specifications

| | |
|----------------------------|--|
| 1D Code types | Code 39, Code 93, Code 128, EAN128, Codabar, Plessey, Code 32, Code 11, MSI, GS1 DataBar linear codes, IATA, Follet 2/5, Code 4, Code 5, Codablock F, UPC/EAN, UPC/EAN P2/P5 add ons, UPC/EAN Coupons, ISBN, Code 39 Full ASCII, Interleaved 2/5, Standard 2/5, Code 39 CIP, Industrial 2/5, Datalogic 2/5 |
| Approvals | RoHS |
| Battery | Lithium-ion 3350 mA |
| Charge time | 4.5 hrs |
| Color | Black, Yellow |
| Dimension (mm) | 212 x 110 x 74 |
| Drop resistance | Withstands 50 drops from 6.6ft onto concrete surface |
| Extra Features | Removable battery |
| Humidity | 0-95% (Non-condensing) |
| Interface | Keyboard wedge, RS-232, USB |
| IP Class | IP65 |
| Kit | No |
| Light Source | Green LED |
| Readable code types | 1D / Linear Codes |

| | |
|--|--|
| Reading Angle Window | Pitch: +/-75°; Tilt: +/- 45°; Skew: +/-70° |
| Reads per charge | 60000 |
| Resolution | 2.5 mils |
| Temperature range bearing, from | -40 |
| Temperature range bearing, to | 70 |
| Temperature range from | -20 |
| Temperature range to | 50 |
| Weight | 405 |
| Wireless | Yes |
| Wireless Technology | Datalogic STAR Cordless System |