

## DATALOGIC QUICKSCAN I QD2131

QD2131-BKK1

QuickScan I QD2131, Linear Imager, USB Kit, Black  
(Cable)

- Detects 1D code types
- 'Green spot' technology
- 400 reads/sec
- Interfaces: Keyboard wedge, OEM (IBM) USB, RS-232, USB



### Product description

### Specifications

|                                  |  |
|----------------------------------|--|
| <b>1D Code types</b>             | Auto discriminates all standard 1D codes                 |
| <b>Approvals</b>                 | RoHS   |
| <b>Color</b>                     | Black  |
| <b>Dimension (mm)</b>            | 163 x 91 x 41  |
| <b>Drop resistance</b>           | Withstands repeated drops from 5ft onto concrete surface |
| <b>Extra Features</b>            | Kit includes: Scanner and 90A052258 Cable                |
| <b>Humidity</b>                  | 90% (Non-condensing)                                     |
| <b>Immunity To Ambient Light</b> | 0 - 120,000 lux  |
| <b>Interface</b>                 | Keyboard wedge, OEM (IBM) USB, RS-232, USB               |
| <b>IP Class</b>                  | IP42   |
| <b>Kit</b>                       | Yes  |
| <b>Light Source</b>              | Red LED 610-650 nm                                       |
| <b>Output current</b>            | 400mA @ 5VDC   |
| <b>Readable code types</b>       | 1D / Linear Codes  |
| <b>Reading Angle Window</b>      | Pitch: +/-65°; Tilt: +/- 45°; Skew: +/-70°               |
| <b>Reading Speed</b>             | 400 reads/sec  |

|                                 |                  |
|---------------------------------|------------------|
| Resolution                      | 0.102mm / 4 mils |
| Temperature range bearing, from | -40              |
| Temperature range bearing, to   | 70               |
| Temperature range from          | 0                |
| Temperature range to            | 50               |
| Weight                          | 150              |
| Wireless                        | No               |