

DATALOGIC GRYPHON™ I GD4500

GD4590-HCK10-BPOC

Gryphon I GD4590, 2D Mp, USB/RS-232/Wedge,
BPOC Kit, HC (Scanner, USB Cable)

- Detects 1D/2D code types
- Image sensor: 1MP, 1280 x 800 pixels
- Disinfectant ready enclosures
- Interfaces: USB type C, USB, RS-232, multi interface



Product description

The Gryphon GD4500 product series from Datalogic represents the premium level of hand held scanners for general purpose applications. The dedicated optics specifically designed and uniquely tailored for the Gryphon, exploit a megapixel sensor and distinctive technology with highly visible warm-white illumination to achieve outstanding omnidirectional reading performance. Because of the increased motion tolerance, codes placed on fast-moving objects can be easily and quickly captured, creating the ideal hand held scanner for tasks requiring high throughput.

Whether in department or specialty stores, in hyper stores and supermarkets, convenience stores or groceries, the Gryphon GD4500 scanner fits most any retail in-store requirement for POS checkout.

A specialized model with red illumination provides the ultimate Digimarc® Barcode reading, as Digital Watermarking has become a new reality for top retailers.

In the dedicated models with Disinfectant-Ready and Anti-Microbial enclosures, the Gryphon I GD4500 scanner is the ideal companion for Healthcare applications such as in laboratories and bedside point-of-care.

Specifications

| | |
|-----------------------|---|
| 1D Code types | Auto discriminates all standard 1D codes |
| 2D Code Types | Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code, Dot Code |
| Approvals | RoHS |
| Color | White |
| Dimension (mm) | 166 x 68 x 109 |

| | |
|--|---|
| Drop resistance | Withstands repeated drops from 6ft on concrete surface |
| Extra Features | Kit includes: Scanner and USB Cable 90A052278 |
| Humidity | 0-95% (Non-condensing) |
| Immunity To Ambient Light | 0 - 100,000 lux |
| Interface | USB type C, USB, RS-232, Keyboard wedge multi interface |
| IP Class | IP52 |
| Kit | Yes |
| Light Source | Warm white |
| Output current | <400mA @ 5V, <200mA @ 12V |
| Postal Code Types | China Post, IMB, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), UK Postal, Australia Postal, Japan Postal |
| Readable code types | 1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes |
| Reading Angle Window | Pitch: +/-65°; Tilt: 360°; Skew: +/-65° |
| Resolution | 0.102 mm / 4mils |
| Sensor type | 1 Megapixel: 1280 x 800 pixels |
| Stacked Code Types | EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites |
| Temperature range bearing, from | -40 |
| Temperature range bearing, to | 70 |
| Temperature range from | 0 |
| Temperature range to | 50 |
| Weight | 161 |
| Wireless | No |