

DATALOGIC MATRIX 220 IMAGER

MATRIX220352-010

937900000, 1.2MP, White LED, 7mm Lens

- 1.2 MP resolution
- Detects 1D and 2D code types
- Up to 45 fps
- Integrated communication via Ethernet 10/100 Mbit/s:
Fieldbus PROFINET-IO, Ethernet IP, Modbus TCP, Serial
RS-232/RS422FD, OPC UA



Product description

The Matrix 220 compact barcode imager offers outstanding performance on standard and DPM codes in a compact and lightweight body. Offering higher performance than a MATRIX120 and still in a compact body the MATRIX220 is ideal for more demanding applications.

Superior performance is provided thanks to a new multi core image processing platform and high resolution 1.2MP sensor, embedded fieldbus and PoE capabilities it is an ideal choice for high speed scanning in compact applications.

The Matrix 220 is excellent for DPM and highly reflective surface scanning with its diffuse multi LED polarised version or it can be used with the standard white LEDs for easier to read applications.

As with all of the Matrix series its fully compatible with the easy to use DL.CODE software suite.

Also the MATRIX220 is uniquely designed to be placed on the end of a robot arm due to its size, performance on DPM codes and PoE capabilities.

Specifications

Colour LED	White
Connection	M12 17P + ETH
Digital Inputs	2
Digital Outputs	3
Dimension (mm)	78 x 47 x 38
Distance Max	400
Distance Min	40
Frame Rate Max	45
Integrated Communication Interface	Ethernet 10/100 Mbit/s: Fieldbus PROFINET-IO, Ethernet IP, Modbus TCP, Serial RS-232/RS422FD, OPC UA
IP Class	IP67, IP65
Multi Label Reading	Yes

Power Consumption	4.2
Programming Options	DL.CODE, Host Mode programming, X-PRESS
Resolution	1280 x 960 (1.2 megapixel)
Sensor size	1/3"
Shutter type	Global
Supply voltage	10-30 V DC
Temperature range bearing, from	-20
Temperature range bearing, to	70
Temperature range from	-10
Temperature range to	50
Weight	173
Viewing angle	7mm

