

DATALOGIC POWERSCAN I RETAIL PBT/PM9501

PBT9501-WH-RT
PowerScan Retail PBT9501, Bluetooth, Fixed Battery,
White

- Detects 1D/2D code types
- 864 x 544 image sensor
- 60,000+ reads per charge
- Interfaces: RS-232, USB COM, USB HID Keyboard



Product description

Specifications

Approvals	RoHS, REACH
Battery	Lithium-ion 3550 mAh
Charge time	4.5 hrs
Color	White
Dimension (mm)	212 x 110 x 74
Drop resistance	Withstands 50 drops from 6.6ft onto concrete surface
Extra Features	Fixed battery
Humidity	95% (Non-condensing)
Immunity To Ambient Light	0 - 100,000 lux
Interface	RS-232, USB COM, USB HID keyboard: optional ethernet
IP Class	IP65
Kit	No
Light Source	Red LEDs
Reading Angle Window	Pitch: +/-40°; Tilt: +/- 360°; Skew: +/-40°
Reads per charge	60000
Resolution	1D: 4 mils, 2D: 7.5 mils

Temperature range bearing, from	-40
Temperature range bearing, to	70
Temperature range from	-20
Temperature range to	50
Weight	400
Wireless	Yes
Wireless Technology	Bluetooth Wireless Technology