

## DATALOGIC AV500/900 SERIES

AV500166W

938000007, 16mm, f/6, White LED

- 5MP or 9MP resolution
- Detects 1D and 2D code types
- Up to 32 fps
- Integrated communication via Ethernet TCP/IP, Serial



### Product description

### Specifications

<b>1D Code types</b>	Code 39, Code 93, Code 128, Codabar, Pharmacode, Code 32, GS1-128, MSI, Code 39 Full ASCII, Interleaved 2/5, Standard 2/5, Matrix 2/5
<b>2D Code Types</b>	Data Matrix, MaxiCode, Micro QR Code, QR Code
<b>Colour LED</b>	White
<b>Dimension (mm)</b>	200 x 126 x 130
<b>Frame Rate Max</b>	32
<b>Integrated Communication Interface</b>	Ethernet TCP/IP, Serial
<b>IP Class</b>	IP65
<b>Material of body</b>	Die cast aluminium
<b>Postal Code Types</b>	Aztec Code, KIX Post, Planet Code, Postnet, Swedish Post, Australia Postal, Japan Postal, Royal Mail 4 State Customer, Postnet (+BB), Intelligent Mail
<b>Programming Options</b>	e-GENIUS multi-language, browser based, on board HTML web server interface
<b>Readable code types</b>	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
<b>Resolution</b>	5 MP
<b>Sensor type</b>	CMOS
<b>Stacked Code Types</b>	Micro PDF 417, PDF 417, EAN 8-13 - UPC-A/E (Including Addon 2 and 5), GS1 Databar Family

Supply voltage	24 V DC
Temperature range bearing, from	-20
Temperature range bearing, to	70
Temperature range from	0
Temperature range to	50
Type of lens	16mm C-Mount
Weight	2900