

DATALOGIC PBT/PM9501-DPM SERIES

PBT9501-DPMRB

PowerScan PBT9501, BT, Direct Part Marking EVO,
Removable Batt

- Detects 1D and 2D code types
- Reads 1D codes up to 2.5mil and 2D codes up to 4 mil
- Direct part marking reading capabilities
- Interfaces: RS-232, USB, Keyboard wedge multi-interface, Ethernet



Product description

Specifications

| | |
|--|---|
| Approvals | RoHS |
| Battery | Lithium-Ion: 3350 mAh |
| Charge time | 4.5hrs |
| Color | Yellow, Black |
| Dimension (mm) | 212 x 110 x 74 |
| Drop resistance | Withstands 50 drops from 1.2m / 3.9ft onto concrete surface |
| Humidity | 0-95% (Non-condensing) |
| Immunity To Ambient Light | 0-100,000 lux |
| Interface | Keyboard wedge, RS-232, USB |
| IP Class | IP65 |
| Kit | No |
| Light Source | 630-680nm VLD |
| Reading Angle Window | Pitch: +/-40°; Tilt: +/- 360°; Skew: +/-40° |
| Reads per charge | 60000 |
| Resolution | 4 mils |
| Temperature range bearing, from | -40 |
| Temperature range bearing, to | 70 |
| Temperature range from | -20 |
| Temperature range to | 50 |

| | |
|----------------------------|-------------------------------|
| Weight | 400 |
| Wireless | Yes |
| Wireless Technology | Bluetooth Wireless Technology |