DATALOGIC PBT/PM9501-DPM SERIES

PBT9501-DPMRB
PowerScan PBT9501, BT, Direct Part Marking EVO, Removable Batt



- Detects 1D and 2D code types
- Reads 1D codes up to 2.5mil and 2D codes up to 4 mil
- Direct part marking reading capabilities
- Interfaces: RS-232, USB, Keyboard wedge multi-interface, Ethernet

PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	RoHS
Battery	Lithium-Ion: 3350 mAh
Charge time	4.5hrs
Color	Yellow, Black
Dimension (mm)	212 x 110 x 74
Drop resistance	Withstands 50 drops from 1.2m / 3.9ft onto concrete surface
Humidity	0-95% (Non-condensing)
Immunity To Ambient Light	0-100,000 lux
Interface	Keyboard wedge, RS-232, USB
IP Class	IP65
Kit	No
Light Source	630-680nm VLD
Reading Angle Window	Pitch:+/-40°; Tilt: +/- 360°; Skew: +/-40°
Reads per charge	60000
Temperature range bearing, from	-40
Temperature range bearing, to	70
Temperature range from	-20
Temperature range to	50
Weight	400
Wireless	Yes

Wireless Technology	Bluetooth Wireless Technology