DATALOGIC POWERSCAN PBT9501-AR SERIES

PBT9501-ARRB
PowerScan PBT9501, Bluetooth, Auto Range, Removable Battery



- Detects 1D and 2D codes
- Reads 1D codes up to 3 mil and 2D codes up to 4 mil
- 40,000+ reads per charge
- Interfaces: Keyboard wedge, RS-232, USB

PRODUCT DESCRIPTION

SPECIFICATIONS

Approvals	RoHS
Battery	Lithium-Ion: 3350 mAh
Charge time	4.5hrs
Color	Black/yellow
Dimension (mm)	212 x 110 x 74
Drop resistance	Withstands 50 drops from 2m / 6.5ft to concrete
Humidity	0-95% (Non-Condensing)
Immunity To Ambient Light	Immune to light exposure in offices/facilities and direct exposure to sunlight
IP Class	IP65
Kit	No
Light Source	LED
Reading Angle Window	Pitch: +/-80°; Roll (tilt): +/-180°; Skew (Yaw): +/-60°
Reads per charge	40000
Temperature range bearing, from	-40
Temperature range bearing, to	70
Temperature range from	-20

Temperature range to	50
Weight	460
Wireless	Yes
Wireless Technology	Bluetooth Wireless Technology