

DATALOGIC MATRIX 300N IMAGER

OBSOLETE - Please contact vision@oem.co.uk for possible replacements

MATRIX300N435010

OBSOLETE - Please contact vision@oem.co.uk for more information



- 1.3 MP and 2 MP resolutions
- Detects 1D and 2D code types
- Up to 60 fps
- Integrated communication via Ethernet 10/100: Ethernet IP, TCP/IP, UDP, FTP, MODBUS TCP, RS232/RS422/RS485 On-board PROFINET-IO as standard

Product description

The MATRIX300N has been made obsolete and superseded by [MATRIX320N 2MP](#) OR [MATRIX220 X 1.2MP](#). Please contact vision@oem.co.uk for direct replacements.

Matrix 300N™ is the next-generation, compact imager in the Matrix family. This high resolution sensor has ultra-fast image acquisition, at 1.3 megapixel and a frame rate of 60 frames per second. The Matrix 300N™ is ultra-compact, purpose built for superior performance on high speed and Direct Part Marking (DPM) applications.

For the electronic focus control the optical system incorporates a liquid lens module, as a result the reader offers automatic focus adjustment without the addition of moving parts.

The innovative design of integrated illuminators embedded over the entire front surface allows for bright, uniform illumination. Suitable for illumination on normal, etched, reflective or textured surfaces due to the lighting design using both bright and dark field patterns.

The small dimensions of the Matrix 300N™ and rotating connector makes it ideal for integrating into small, tight spaces, as well as the M12, 4 pole connections making for easy integration into existing systems.

Additionally the compact flexible design offers cost effective communication options with Power over Ethernet (POE) connection through standard ethernet connection. other connectivity options include PROFINETIO and ETHERNET/IP, eliminating external communication boxes or converters.

Specifications

Digital Inputs	2
Digital Outputs	3
Dimension (mm)	95 x 54 x 43
Extra Features	Narrow angle optics
Frame Rate Max	60
Integrated Communication Interface	Ethernet 10/100, RS-232/RS422/RS485
IP Class	IP67
Power Consumption	5
Programming Options	Windows-based SW (DL.CODE) via Ethernet
Resolution	1280 x 1024 (1.3MP)
Shutter type	Global
Supply voltage	10-30 V DC
Temperature range bearing, from	-20
Temperature range bearing, to	70
Temperature range from	0
Temperature range to	50
Type of lens	Manual focus
Weight	238
Viewing angle	24° (16mm)

