

BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA2040-180KC

Ace CameraLink, CMV4000 1" CMOS, 180fps, Colour, C-Mount



- VGA to 20 Mpixels
- Frame Rate up to 751 fps
- CMOS Sensors with NIR function
- Camera Link with PoCL
- Very small housing

Product description

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

Specifications

| | |
|------------------------------|-----------------------------|
| Approvals | CE, FCC, GenICam, RoHS, EAC |
| Frame Rate Max | 180 |
| Height | 29 |
| Interface | Camera Link |
| IP Class | IP30 |
| Length | 43.5 |
| Lens Barrel | C-mount |
| Mono/Color | Color |
| Operating temperature | 0°C ... 50°C |
| Pixel size | 5.5 x 5.5 |
| Power Consumption | 3 |
| Resolution | 4MP |

| | |
|-----------------|----------------|
| Resolution Max | 2046 x 2046 px |
| Sensor model | CMV4000 |
| Sensor size | 1" |
| Sensor supplier | ams |
| Sensor type | CMOS |
| Shutter type | Global |
| Weight | 100 |
| Width | 29 |

