## BASLER ACE GIGE USB3.0 AND CAMERALINK CAMERAS

Ace Classic, Ace U and Ace L

ACA640-121GM Ace U GigE Camera, ICX618 1/4" CMOS, 134fps, Mono, C-Mount

- VGA to 20 Mpixels
- Frame Rate up to 751 fps
- CMOS Sensors with NIR function
- · Camera Link with PoCL
- · Very small housing



## Product description

Basler Ace Cameras, launched in 2009, are the smallest GigE camera on the market, also available with USB3.0 and Camera Link interface. With a small housing of only 29 x 29mm, the ace is suitable for a large range of vision applications, even where space is limited. There are over 130 models in the Ace range, split is Ace Classic, Ace U and Ace L. All featuring a range of resolutions from VGA to 20mp, speeds of up to 751 fps and sensors from a range of suppliers

Ace Classic model cameras have an excellent price/performance ratio and also feature a range of comprehensive sensors, including, CMOS from CMOSIS, e2V, ON Semiconductor (MT series) and CCD from Sony. The Ace classic range is available in GigE, USB3.0 and CameraLink.

Ace U cameras have the same compact footprint of the Ace Classic range (29 x 29mm), with the addition of unique PGI feature set from Basler and new CMOS sensors, in GigE and USB3.0 interfaces.

Ace L cameras feature the same additional firmware as Ace U but with high resolution 9 and 12mp Sony Pregius CMOS sensors, and optical formats above 1", to accommodate these larger sensors the Ace L is slightly larger with a footprint of 40mm x 30mm. With frame rates up to 40fps, the Ace L is available in GigE and USB3.0.

## Specifications

| Approvals             | CE, FCC, GenlCam, GigE Vision, RoHS, UL, EAC |
|-----------------------|--|
| Digital Inputs        | 1  |
| Digital Outputs       | 1  |
| Frame Rate Max        | 134  |
| Height                | 29   |
| Interface             | GigE   |
| IP Class              | IP30   |
| Length                | 42   |
| Lens Barrel           | C-mount                                      |
| Mono/Color            | Mono   |
| Operating temperature | 0°C 50°C                                     |
| Pixel size            | 5.6 x 5.6                                    |

| Power Consumption | 2.7                |
|-------------------|--------------------|
| Resolution        | VGA                |
| Resolution Max    | 659 x 494 px       |
| Sensor model      | ICX618 Replacement |
| Sensor size       | 1/4"               |
| Sensor supplier   | Sony               |
| Sensor type       | CMOS               |
| Shutter type      | Global             |
| Weight            | 90                 |
| Width             | 29                 |