BASLER ACE 2 BASIC & PRO CAMERAS

5GigE, GigE & USB3.0

A2A4504-27G5CBAS Ace 2 Basic 5GigE Camera, IMX541 1.1" CMOS, Colour





- Up to 24.4MP resolutions
- 5GigE, GigE and USB3.0 interfaces
- IMX sensor
- LED Status
- Robust M8 contact

Product description

Basler Ace 2 series cameras include 2 product lines tailored to different vision needs, Ace 2 Basic and Ace 2 Pro. Both include GigE and USB3.0 variations, resolutions from 2.3MP to 24MP and up to 168fps with Compression Beyond or 160fps standard. The Ace 2 Basic and Pro cameras still have unbeatable price/performance ratio, featuring optimised hardware, state of the art CMOS sensor technology from Sony and fast, cost-effective software integration.

The cameras in the Basic series are designed to meet the standard requirements of machine vision systems in terms of functionality and economy, while maintaining the familiar reliability of Basler products.

The Pro Series cameras are suitable for applications where the camera requires more demanding tasks and maximum performance with the new Compression Beyond and Pixel Beyond and PGI features.

Compression Beyond allows you to compress image data directly from the camera's FPGA in real time without affecting image quality. The desired data can also be stored in full resolution in compressed form while saving storage space in the system.

With the Pixel Beyond feature, you can change the pixel size of the image and thus affect important cell characteristics such as resolution and signal-to-noise ratio (SNR). In this way, other cell models can be easily simulated, for example, redesign can be facilitated without having to reconfigure the entire imaging system.

Specifications

Approvals	CE, FCC, GenlCam, EAC, RoHS, GigE Vision
Digital Inputs	1
Frame Rate Max	27
Height	29
Interface	5GigE
IP Class	IP30
Length	55.5
Lens Barrel	C-Mount
Mono/Color	Color
Operating temperature	0°C 50°C
Pixel Beyond	No

Pixel size2.74 x 2.74Resolution0.2MPResolution Max4504 x 4504 pxSensor modelMX541Sensor size1.1°Sensor supplierSonySensor typeGlobalMutter type100Wight29		
Resolution Max4504 x 4504 pxSensor modelIMX541Sensor size1.1"Sensor supplierSonySensor typeCMOSShutter typeGlobalWeight100	Pixel size	2.74 x 2.74
Sensor modelIMX541Sensor size1.1"Sensor supplierSonySensor typeCMOSShutter typeGlobalWeight100	Resolution	20.2MP
Sensor size1.1"Sensor supplierSonySensor typeCMOSShutter typeGlobalWeight100	Resolution Max	4504 x 4504 px
Sensor supplier Sony Sensor type CMOS Shutter type Global Weight 100	Sensor model	IMX541
Sensor type CMOS Shutter type Global Weight 100	Sensor size	1.1"
Shutter type Global Weight 100	Sensor supplier	Sony
Weight 100	Sensor type	CMOS
-	Shutter type	Global
Width 29	Weight	100
	Width	29