

BASLER PULSE - COMPACT USB3.0 CAMERAS

PUA1600-60UC/CS
USB 3.0 Camera-e2V EV76C570, 1/1,8" CMOS, 60 fps,
2 MP, CS

- 1.2 - 5 Mpixel
- Elegant design
- Compact size
- USB3.0 Vision compatible



Product description

The Basler pulse cameras is developed to meet the requirements of a broad variety of vision applications, it combines the established Basler quality with a sophisticated design.

The pulse series stands out, starting with a sharp, robust metal housing including tripod adapter and a CS-mount which easily can be converted to C- or S-mount. pulse is equipped with the USB3 Vision plug and play interface and offers great stability and impressively low power consumption. These and other features make the Basler pulse a very compact solution for easy system integration as well as for the switch from analog to digital vision technology.

With its new generation of CMOS sensor technology, the pulse series offers global shutter and rolling shutter options, making it the natural choice for users who need most pristine and colorful images together with live footage.

Specifications

Approvals	CE, FCC, GenICam, RoHS, UL, USB3 Vision, EAC
Frame Rate Max	60
Interface	USB 3.0
Length	28.2
Lens Barrel	CS-mount
Mono/Color	Color
Operating temperature	0°C ... 50°C
Pixel size	4.5 x 4.5
Power Consumption	1.3
Resolution	2MP
Resolution Max	1600 x 1200 px
Sensor model	EV76C570
Sensor size	1/1.8"
Sensor supplier	e2v

Sensor type	CMOS
Shutter type	Global
Weight	60

